

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

DANLAID EXCEL FLOOR

SYNONYMS

"floor levelling compound cement"

PRODUCT USE

Floor levelling compound.

SUPPLIER

Company: Danlaid Contracting Pty Ltd

ABN: 76 079777914

Address:

43 DeHavilland Road

Mordialloc

VIC 3195

Aust.

Telephone: +61 3 8514 6300

Fax: 03 8514 6310

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

None under normal operating conditions.

SAFETY

Do not breathe dust.

Wear eye/ face protection.

Use only in well ventilated areas.

Keep container in a well ventilated place.

Take off immediately all contaminated clothing.

In case of contact with eyes, rinse with plenty

of water and contact Doctor or Poisons

Information Centre.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
graded sand	14808-60-7.	30-60
calcium aluminat cement	65997-16-2	10-30
calcium carbonate	471-34-1	1-19
additives, unregulated		1-10

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

continued...

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 2 of 10

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

Brush off dust.

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear breathing passages.
- Ask patient to rinse mouth with water but to not drink water.
- Seek immediate medical attention.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.

continued...

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 3 of 10

Section 5 - FIRE FIGHTING MEASURES

- Not considered a significant fire risk, however containers may burn.

FIRE INCOMPATIBILITY

None known.

HAZCHEM: None

Personal Protective Equipment

Breathing apparatus.

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety glasses.
- Use dry clean up procedures and avoid generating dust.
- Sweep up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

Moderate hazard.

- CAUTION: Advise personnel in area.
- Alert Emergency Services and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.
- Prevent, by any means available, spillage from entering drains or water courses.
- Recover product wherever possible.
- IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
- ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise Emergency Services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

graded sand	50 mg/m ³
calcium carbonate	15 mg/m ³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

graded sand	0.25 mg/m ³
calcium carbonate	15 mg/m ³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

graded sand	0.15 mg/m ³
calcium carbonate	15 mg/m ³

continued...

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 4 of 10

Section 6 - ACCIDENTAL RELEASE MEASURES

The threshold concentration below which most people will experience no appreciable risk of health effects:

graded sand	0.15 mg/m ³
calcium carbonate	15 mg/m ³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

None known.

STORAGE REQUIREMENTS

- Keep dry.
- Store under cover.
- Protect containers against physical damage.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC
Australia Exposure Standards	calcium aluminate cement (Inspirable dust)		10					

continued...

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 5 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC
Australia Exposure Standards	(Not specified) calcium carbonate (Calcium carbonate (a))		10					

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
graded sand	50	

MATERIAL DATA

Not available. Refer to individual constituents.

INGREDIENT DATA

GRADED SAND:

NOTE: This product contains negligible amount of respirable dust.

CALCIUM CARBONATE:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus

increasing the risk of overexposure.

The TLV-TWA is thought to be protective against the significant risk of physical irritation associated with exposure.

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or

continued...

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 6 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	--	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Grey powder; partly soluble in water.

PHYSICAL PROPERTIES

Molecular Weight: Not Applicable
Melting Range (°C): Not Available
Solubility in water (g/L): Partly Miscible
pH (1% solution): Not Available
Volatile Component (%vol): Not Applicable

Boiling Range (°C): Not Applicable
Specific Gravity (water= 1): Not Available
pH (as supplied): Not Applicable
Vapour Pressure (kPa): Not Applicable
Evaporation Rate: Not Applicable

continued...

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 7 of 10

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Relative Vapour Density (air=1): Not Applicable

Lower Explosive Limit (%): Not Applicable

Autoignition Temp (°C): Not Available

State: Divided Solid

Flash Point (°C): Not Applicable

Upper Explosive Limit (%): Not Applicable

Decomposition Temp (°C): Not Available

Viscosity: Not Applicable

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
-

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Solution of material in moisture on the skin, or perspiration, may increase irritant effects.

Handling wet cement can cause dermatitis. Cement when wet is quite alkaline and this alkali action on the skin contributes strongly to cement contact dermatitis since it may cause drying and defatting of the skin which is followed by hardening, cracking, lesions developing, possible infections of lesions and penetration by soluble salts.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

INHALED

Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.

continued...

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 8 of 10

Section 11 - TOXICOLOGICAL INFORMATION

CHRONIC HEALTH EFFECTS

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on X-ray.

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

GRADED SAND:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances. No data of toxicological significance identified in literature search.

CALCIUM ALUMINATE CEMENT:

No data of toxicological significance identified in literature search.

CALCIUM CARBONATE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (Rat) LD50: 6450 mg/kg

IRRITATION

Skin (rabbit): 500 mg/24h- Moderate

Eye (rabbit): 0.75 mg/24h - SEVERE

The material may produce severe irritation to the eye causing pronounced inflammation.

Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

No evidence of carcinogenic properties.

No evidence of mutagenic or

teratogenic effects.

MATERIAL	CARCINOGEN	REPROTOXIN	SENSITISER	SKIN
graded sand	IARC:1			

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: graded sand

Category: 1

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

continued...

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 9 of 10

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,
IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

graded sand (CAS: 14808-60-7) is found on the following regulatory lists;

- Australia - New South Wales Hazardous Substances Prohibited for Specific Uses
- Australia - New South Wales Hazardous Substances Requiring Health Surveillance
- Australia - South Australia Hazardous Substances Requiring Health Surveillance
- Australia - Tasmania Hazardous Substances Prohibited for Specified Uses
- Australia - Tasmania Hazardous Substances Requiring Health Surveillance
- Australia - Western Australia Hazardous Substances Requiring Health Surveillance
- Australia Exposure Standards
- Australia Hazardous Substances Requiring Health Surveillance
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia Occupational Health and Safety (Commonwealth Employment) (National Standards)
- Regulations 1994 - Hazardous Substances Requiring Health Surveillance
- International Agency for Research on Cancer (IARC) Carcinogens
- OECD Representative List of High Production Volume (HPV) Chemicals

calcium aluminate cement (CAS: 65997-16-2) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)

calcium aluminate cement (CAS: 12042-68-1) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)

calcium carbonate (CAS: 471-34-1) is found on the following regulatory lists;

- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia Therapeutic Goods Administration (TGA) Substances that may be used as active ingredients in Listed medicines
- CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals

calcium carbonate (CAS: 1317-65-3) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia Inventory of Chemical Substances (AICS)
- OECD Representative List of High Production Volume (HPV) Chemicals

No data available for calcium carbonate as CAS: 13397-26-7, CAS: 15634-14-7.

continued...

DANLAID EXCEL FLOOR

Chemwatch Material Safety Data Sheet

Issue Date: 12-Jul-2007

NC317ECP

CHEMWATCH 4958-16

Version No:4

CD 2007/2 Page 10 of 10

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name

calcium aluminate cement

calcium carbonate

CAS

65997- 16- 2, 12042- 68- 1

471- 34- 1, 13397- 26- 7, 15634- 14- 7, 1317-
65- 3

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 12-Jul-2007

Print Date: 12-Jul-2007